

PUBLIC WORKS AGENCY

P.O. Box 1070 / 777 N. Colusa Street

Willows, CA 95988

530.934.6530 Fax 530.934.6533

www.countyofglenn.net



ADDENDUM NO. 1

to

Glenn County Pothole Repair Services **Request for Proposal**

Submittal Deadline: October 3, 2019

September 11, 2019

To All Bidders:

The following is Addendum 1 to Glenn County's Request for Proposal for On-Call Pothole Repair Services. Please acknowledge the receipt of this addendum on your proposal. The text below summarizes the amendments in the Scope of Services and Fee Schedule to the Request for Proposal (RFP). Additional services requested and the revised Fee Schedule are incorporated as part of this addendum.

1. Additional services are included to the previous Scope of Services to perform Digout Repairs of failed road base material and damaged pavement.
2. Revised Fee Schedule with addition of bid item for "Digout Repairs"

Attached:

Additional Scope of Work – Added
Fee Schedule – Revised

ADDITIONAL SCOPE OF SERVICES

The services to be provided for Digout Repairs of failed road base material and damaged pavement is as follows:

1. The Contractor shall remove existing asphalt concrete surfacing and any unsuitable base material, and replace with hot mix asphalt (HMA). The County shall determine the exact limits of the digout.
2. Areas designated by the County shall be dug out to a depth determined by the County, removed, and replaced with the same thickness of HMA. The final lift of HMA must be 2 inches thick or greater. The common practice of capping dig outs with a thin lift of asphalt is not acceptable.
3. All edges shall be saw-cut or milled. If a milling machine is used, all sloping edges shall be chipped to a vertical face. Exposed edges shall be protected against breakage with timbers or HMA mix whenever a roller enters or leaves the repair spot.
4. The underlying material to remain in place shall be recompact to 95 percent minimum relative compaction to a depth of 6 inches below the bottom of the repair. If additional subgrade, subbase, or base material is needed, it will be supplied and delivered to the digout location by the County.
5. After compaction and prior to the placing of hot mix asphalt, the vertical edges of the existing pavement shall receive a tack coat.
6. The finished repair shall conform to the surrounding grade and contour and shall not trap water or present a visible hump.
7. In the event that the underlying material is deemed unsuitable by the County, it shall be excavated and hauled to a location chosen by the County. The limits of removal shall be designated by the County. The resulting space shall be filled with a single lift of asphalt concrete.

Note: All the above services stated under Scope of Services will be executed in addition to the previous Scope of Services in the published Request for Proposal (RFP).

**UNIT PRICES FOR THE
POTHOLE REPAIR SERVICES**

The undersigned proposes to furnish all labor, material, equipment, supervision, delivery, insurance, traffic control, safety items, and all other related expenses per the attached specification for the price indicated below.

The following Unit Price shall be valid through December 31, 2020*

Description	Unit	\$/unit
Hot Mix Asphalt 3/8"	CY	\$
Pothole Repair Services	HR	\$
Digout Repairs	SQ. FT.	\$

**Added per Addendum #1*

COMPANY: _____

ADDRESS: _____

CITY, STATE, ZIP: _____

SIGNATURE: _____

TITLE: _____

PHONE#: _____

FAX#: _____

EMAIL: _____

UNSIGNED PROPOSALS WILL NOT BE CONSIDERED

NOTE: COMPANY'S BRIEF HISTORY, SERVICES, PROVIDED AND AGENCY REFERENCES SHALL BE INCLUDED ON A SEPARATE PIECE OF PAPER